



AMERICAN-MARSH PUMPS

"PUMPS AND PUMPS ONLY SINCE 1873"

460 Series Process Pumps

Flows to: 7,400 GPM

Heads to: 985 Feet

Temperatures to: 800° F


130 Years of Pump Manufacturing

American-Marsh Pumps, one of the oldest pump lines in America, are pump products steeped in heritage. Since 1873, the American-Marsh line of pumps has withstood the test of time. During the last 130 years, over 100 varieties of pumps have been designed and built. From steam pumps to centrifugal pumps, American-Marsh pumps have been built to meet the ever changing requirements of society. Over the last century through continuous product development, more American-Marsh models have been retired than most other pump manufacturers have ever produced. Hundreds of thousands of pumps have been made, all designed for longevity, allowing many of them to continue servicing customers over 50 years.

All of our pumps have three superior characteristics; Design, Performance, and Durability. Our engineering department, which includes an in-house pattern shop, designs each pump so that installation and maintenance is easy. Our performances are engineered to meet or beat the competition in each category. For 130 years, American-Marsh Pumps products have

provided cost effective solutions by building pumps to last. Durability by design is always the most cost effective solution. From engineering and design to final assembly, experienced people control each step of the manufacturing process with quality control inspections performed at each step. All pumps shafts are heat straightened. All impellers are computer balanced. Pump testing is done in our new state of the art test facility. All of these factors ensure you receive consistent quality product every time.

American-Marsh Pumps has provided quality pump products for over 130 years. At American-Marsh Pumps, we know that long life and superior performance are the keys to satisfied customers. By understanding your needs, we can design products that meet those needs. Our product family reflects years of customer input, product upgrades, redesign and new product development, all focused on meeting and exceeding your expectations.





Specifications OSD & OSO Series

Casing: The casing is constructed of high tensile cast steel or other specified material. It is of the volute type, carefully and accurately proportioned to permit smooth flow and to convert high velocity energy of the fluid as it leaves the impeller into pressure. Suction and discharge nozzles are flanged and are cast integral with the volute.

OSD Models The casing has cast integral feet standard and the discharge port is of the vertical centerline type. The casing assembly fully meets ANSI B73.1M dimensional requirements. Necessary vent and drain openings can be provided upon request. Low Flo models feature concentric casings that minimize shaft deflection and pump vibration.

OSO Models The casing features centerline support with jacketed risers for high temperature applications. The casing assembly is of the centerline support with renewable case wear ring and running clearances designed for high temperature operation.

Impeller: The impeller is of the reverse vane, end suction type, casted in one piece of cast steel or other specified material. Running clearances need to only be adjusted between the back of the impeller and the casing adapter. This design allows for repeatable factory tolerances, all of which can be adjusted on the bench, not just in the field. All impellers are hydraulically and dynamically balanced prior to assembly. OSO impellers are balanced to ISO Grade G1.0 to meet the toughest hydraulic conditions. Front semi-open impellers can be supplied upon request. All models meet the stringent performance requirements of ANSI B73.1M. American-Marsh also offers 4 Low-Flow models to meet difficult low-flow/high-head process applications.


Shaft: The shaft is of high strength steel or other specified material, ground to accurate dimensions and polished to a smooth surface. It is designed for extra stiffness to avoid all critical speeds in operation. OSD & OSO pumps lead the industry in low L^3/D^4 ratios minimizing shaft deflection at the stuffing box. All OSD & OSO models guarantee less than 0.002" shaft deflection at the seal face location, while in operation. As an option, the shaft can be protected by a shaft sleeve of ample thickness to ensure long life. The shaft sleeve can be supplied in various materials.

Seal Chamber: The seal chamber is available in five (5) different configurations depending on the jobsite

requirement. OSD & OSO pumps feature the Flow Modified (FM) seal chamber that keeps solid matter from collecting in the seal chamber causing premature seal failure. The FM bores are available in a small bore (FMS), a large bore (FML) and a small bore with cast integral gland (FMI), all designed to meet the process requirements of the seal industry. OSD & OSO models can also be supplied in a standard Cylindrical Bore (CB) arrangement. The CB bores are available in a small bore (CBS) and large bore (CBL) both designed to meet the process requirements of the seal industry. Seal chambers have provisions for various flush plan arrangements customizing the seal chamber to meet the requirements of the end user. For abrasive applications, packing with a lantern ring can also be supplied. For high temperature applications all seal chambers can be jacketed to reduce seal chamber temperatures. A wide variety of component and cartridge mechanical seals can be used with OSD & OSO standard components.

Power Frame: The power frame is constructed of high tensile ductile iron and provides support for the inboard and outboard bearings. The outboard bearing is of the double row, angular contact type and the inboard bearing is of the single row, deep groove type for excellent axial and radial load support. For axial adjustment of the impeller, the power frame employs a micro-millimeter adjustment which allows the user to dial back factory tolerances between the impeller and the seal chamber. This re-adjustment of tolerances can be done on the bench, compensating for proper seal setting and eliminating the need to have the casing near for final adjustment. Double lip oil seals ensure that contaminants are kept out of the power frame and optional bearing isolators can be supplied upon request. For extremely crucial applications, magnetic bearing isolators with a poppet breather can be specified, hermetically sealing the power frame. The power frame has an oversized, integral oil sump that provides oil for lubrication to each bearing. A large one inch oil level eye is provided standard on the power frame to visually indicate the oil level. The bearings and shafts are so designed to last up to 61% longer than the competition. With shaft deflection indices surpassing nearly all of the competition, 43-252% greater stiffness is achieved resulting in longer Mean Time Between Planned Maintenance (MTBPM).

Model OSD ANSI Pump



Reverse Vane Impeller



Semi-Open Impeller



Low Flow Impeller


Flows To: 7,400 GPM
Heads To: 985 Feet
Temps To: 500° F

Markets:

-  Chemical
-  Food & Beverage
-  General Industry
-  Marine
-  Mining & Aggregate
-  Oil & Gas
-  Power Generation
-  Petro-Chemical
-  Pharmaceutical
-  Pulp & Paper
-  Water & Wastewater


Power Frame

- Heavy duty ductile iron
- Single row inboard and double row outboard bearings
- Oil lubricated with extra large oil sump
- Oversized oil level eye
- Double lip oil seals
- Top vent/breather
- Optional bearing isolators
- Optional grease lubrication



Power Frame Adjustment

- Micro-millimeter shaft and impeller adjustment
- Accurately set impeller clearance in 15 to 20 seconds
- Optional angular contact bearings for the most demanding applications



Casing

- Standard cast steel or other specified material
- Fully meets ANSI B73.1M standards
- Heavy wall thickness to provide for generous corrosion allowance
- Fully cast integral feet for support when utilizing “back-pull-out” feature
- Centerline discharge transmits residual pipe strain to feet of casing and allows for self venting
- Class 150 pound flat face flanges standard
- Optional 150# raised face, 300# flat face and 300# raised face suction and discharge flanges

Engineered Seal Chambers

- Five (5) seal chambers available depending on application (FML, FMS, FMI, CBL & CBS)
- Extend mechanical seal life
- Utilize less expensive seals and flush plans
- Improve pump reliability
- Optional packing for abrasive applications
- Optional jacketed seal chambers

Shaft

- Designed and sized especially for the pump and its applications
- Investment cast or high alloy bar stock available
- Solid, hook sleeve, friction welded or composite shafts available
- Offset keyways to aid shaft balance
- Runout of <0.001 inches at mechanical seal allows seal faces to run true


Impeller

- Hydraulically balanced one piece investment cast of cast steel or other alloy
- Expertly machined to customer specifications
- Fully balanced prior to assembly
- Exclusive reverse vane design that offers repeatable pump performance
- Optional front semi-open impeller

Alignment

- Four precision machined metal-to-metal fit locations (other manufacturers offer only two)
- Precision machined metal-to-metal bearing carrier reduces stack-ups to improve shaft concentricity

Model OSO Hot Oil Pump



Reverse Vane Impeller



Semi-Open Impeller



Low Flow Impeller


Flows To: 7,400 GPM
Heads To: 985 Feet
Temps To: 800° F

Markets:

-  Chemical
-  Food & Beverage
-  General Industry
-  Marine
-  Mining & Aggregate
-  Oil & Gas
-  Power Generation
-  Petro-Chemical
-  Pharmaceutical
-  Pulp & Paper
-  Water & Wastewater

Power Frame

- Heavy duty ductile iron
- Single row inboard and double row outboard bearings
- Oil lubricated with extra large oil sump
- Oversized oil level eye
- Bearing isolators standard
- Top vent/breather




Power Frame Adjustment

- Micro-millimeter shaft and impeller adjustment
- Accurately set impeller clearance in 15 to 20 seconds
- Optional angular contact bearings for the most demanding applications

Alignment

- Four precision machined metal-to-metal fit locations (other manufacturers offer only two)
- Precision machined metal-to-metal bearing carrier reduces stack-ups to improve shaft concentricity



Casing

- Standard cast steel or other specified material
- Heavy wall thickness to provide for generous corrosion allowance
- Case wear ring standard to extend life of the casing
- Centerline support for high temperature applications
- Jacketed risers to aid in cooling of the fluid chamber
- Back-pull-out for ease in service
- Centerline discharge transmits residual pipe strain to feet of casing and allows for self venting
- Class 300 pound flat face flanges standard
- Optional 300# raised face suction and discharge flanges

Engineered Seal Chambers

- Five (5) seal chambers available depending on application (FML, FMS, FMI, CBL & CBS)
- Extend mechanical seal life
- Utilize less expensive seals and flush plans
- Improve pump reliability
- Optional packing for abrasive applications
- Optional jacketed seal chambers



Shaft

- Designed and sized especially for the pump and its applications
- Investment cast or high alloy bar stock available
- Solid, hook sleeve, friction welded or composite shafts available
- Offset keyways to aid shaft balance
- Runout of <math><0.001</math> inches at mechanical seal allows seal faces to run true

Impeller

- Hydraulically balanced one piece investment cast of cast steel or other alloy
- Expertly machined to customer specifications
- Fully balanced prior to assembly
- Exclusive reverse vane design that offers repeatable pump performance
- Impeller wear ring standard
- Optional front semi-open impeller

OSD & OSO Fluid End




Exclusive reverse vane impeller with balance holes offers important performance enhancing maintenance reducing advantages. Repeatable performance and seal chamber pressures allow repeatable MTBPM cycle.




Front vane, semi-open impeller is fully interchangeable with the reverse vane impeller. Excellent choice for stringy and certain applications requiring high shear against the casing.




Front vane, Low-Flo, semi-open impeller for operation at low flow with minimal thrust loads and vibration. Radial loads are reduced up to 90% and shaft vibration is reduced up to 50% at low flows.




Centerline mounted casings (OSO Hot Oil) are used to reduce loads caused by thermal expansion. Jacketed feet with inlet/outlet ports further assure effective temperature control.



Jacketed standard bore (CBS) is recommended when cooling the seal chamber is the objective.




Jacketed FM chamber is preferred when protection of the process temperature is important.




Only an American Marsh reverse vane impeller offers repeatable performance after wear and impeller adjustment.


An impeller cannot be adjusted to two locations. Seal and bearing life are reduced due to increased loads after wear and maintenance adjustment.

Optional Connections



Item	Part	Typical Size
I	Casing Drain	3/4" (19 mm)-10, 1/2" (13 mm) NPT, 3/4" (19 mm) NPT
II	Suction Nozzle Gage Connection	1/4" (6 mm) NPT
III	Discharge Nozzle Gage Connection	1/4" (6 mm) NPT
IV	Connection for Line to Seal Chamber	1/4" (6 mm) NPT
V	Connection for Line to Seal Chamber	1/4" (6 mm) NPT
VI	Flush Connection for Mechanical Seal	1/4" (6 mm) NPT
VII	Bottom Tap in Seal Chamber	1/4" (6 mm) NPT






FML

Oversized, tapered bore with 8 specially shaped and evenly spaced cast-in flow modifiers. Designed for seals with large gland bolt and gasket circles.

- Single internal cartridge seals.
- Dual internal/external cartridge seals.
- Single internal component seals with flexibly mounted seats.*
- Dual internal “true” tandem cartridge seals.

Note: Bypass flush to internal seal normally not required. Barrier fluid or external flush may apply to dual seals (Plans 52, 53, etc.)




FMS

Same chamber design as FML, but accommodates seals with small gland bolt and gasket circles.

Same seal and flush plan recommendations as for FML.

Single seals with all types of seat mounting configurations can be installed.

FMS design is provided for the convenience of customers with seal standards that include small glands. This design is American-Marsh’s secondary recommendation to the FML.*




FMI

Same chamber design as FMS, but includes a cast-in integral gland.

- Single internal, flexibly mounted seals. Uses sleeve for seal setting and fast installation.
- “Sanitary-type” applications. Less prone to bacteria build up.

Note: Bypass flush is normally not required.



CBL


Oversized, cylindrical step bore design for seals with large gland bolt and gasket circles.

- Dual internal component seals. Isolates the seal chamber from the process. Allows less expensive seal materials. Recommended in tough slurry applications.

Note: Use External Flush Plan 54. Others (i.e., Plans 52, 53) not recommended without close tolerance pumping mechanism.

- Single internal component or cartridge seals when applied with a throat bushing. Usually selected to increase stuffing box pressure above the vapor pressure to avoid cavitation, etc.

Note: Applied with Plan 11, etc.



CBS

Cylindrical bore design for packing arrangements and conventional seals with small gland bolt and gasket circles.

- Dual internal component seals. Isolates the seal chamber from the process. Allows less expensive seal materials. Recommended in tough slurry applications. Allows for thermal convection type flush plans; however pumping ring devices are recommended.

Note: Use External Flush Plan 52, 53, 54

- Single internal component or cartridge seals when applied with a throat bushing. Usually selected to increase stuffing box pressure above the vapor pressure to avoid cavitation, etc.

- Usually preferred over the CBL when jacketing is selected for increased effectiveness in cooling or heating.

Note: Applied with Plan 11, etc.

All seal selections perform best when the faces are located directly within the flush plan, particularly if solids, liquors, or slurries are present. Component seals with clamped seat gland designs locate the seal faces reasonably well. Flexibly mounted seat glands should include the vent and drain option to better locate the seal faces. The FML is always the first choice chamber for maximum self-flush path benefits.

Performance Life Cycle Comparison:

AMP Reverse Vane Impeller With Balance Holes


Effects of Wear

Thrust loads decrease as seal chamber gap widens
Chamber pressure increases as gap widens

Effects of Impeller Adjustment To Seal Chamber

Original pressures and loads re-established after adjustments

Repeatable MTBPM cycle life



Front Vane Open Style Impeller With Pump Out Vanes


Effects of Wear

Thrust loads increase as seal chamber gap widens
Chamber pressure increases as gap widens

Effects of Impeller Adjustment To Seal Chamber


Chamber pressure and bearing loads increase after each adjustment

Non-repeatable MTBPM cycle life




OSD & OSO Power Frame

Larger Oil Sump



Optional Bearing Housing Cooler




Standard OSD Power Frame Features


- Double row, angular contact outbound/single row, deep groove inboard bearings for excellent axial and radial load support
- Double lip oil seals
- Top mounted vent and oil filler
- Trico oiler
- Large on inch diameter reflective sight glass
- Micro-millimeter impeller adjustment
- Optional oil slinger
- Optional bearing isolators
- Optional magnetic drain plug
- Optional shielded and grease lubricated bearings

Shaft Details


- 1 Radiused "sled-runner" keyways improve strength at this stress point.
- 2 Offset keyways aid shaft balance.
- 3 Alloy identification on every shaft and sleeve ensures that the right parts go in every time.
- 4 Large radii fillets add strength.
- 5 Accurate machining under bearings ensures perfect bearing fits without vibration or hot running.
- 6 Run-out of <0.001 in (0.03 mm) at mechanical seal allows seal faces to run true.
- 7 Critical surfaces ground to a surface finish of 16u in (0.4 micron) ensure the secondary sealing ability of mechanical seals.
- 8 Steel power ends handle higher horsepower loads than stainless.
- 9 Minimally radiused edges ensure full contact with impeller for reduced run-out.




Group I Shaft



Group II Shaft




Group III Shaft




* 4 x 6 -10 pump shaft coupling end 1.5000 Ø (38.100 mm)
1.4995 Ø (38.087 mm)

Shaft Deflection Graphs


Group I & II 3500 RPM



Group I & II 1750 RPM



Group III 1750 RPM



American-Marsh Pumps provides the user dependability and durability. by designing pumps with upgraded, heavier-duty components. Durability by design is always the most cost effective solution.

CASING


The casing fully meets ANSI B73.1M dimensional standards and is designed for back pull-out making service easy. The casing is also provided with additional thickness for corrosion allowance. Surfaces are machined to accurate tolerances in our machining centers. Centerline discharge allows for self-venting casings and cast integral feet provide additional support.

BEARINGS

OSD ANSI pumps feature oversized, oil lubricated bearings designed for long life and minimal maintenance. The inboard bearing is of the single row type and the outboard bearing is of the double row type. The power frame utilizes two double lip oil seals to minimize the entrance of contaminants into the oil. MTBPM is drastically increased by using larger bearings and larger shafts allowing for a smaller shaft deflection index all which extends seal life.

IMPELLER RING

The impeller is investment casted out of customer specified material and is of the exclusive reverse vane design. All impellers are dynamically and hydraulically balanced to meet ANSI B73.1M performance standards. Optional semi-open impellers can be supplied upon request.



MECHANICAL SEALS/PACKING

OSD ANSI pumps feature five (5) seal chambers designed to meet extreme services found in today's applications. FML, FMS, FMI, CBL & CBS seal chambers offer the enduser a pump and an engineered seal chamber designed to meet specific fluid and temperature requirements.

SHAFTS

Shafts are available in a wide variety of materials and are sized for minimal shaft deflection. Solid, composite and hook sleeve configurations are available upon request.

OTHER PUMP PRODUCTS

SPLIT CASE

To 44" Discharge
73,000 GPM, 550'

VERTICAL TURBINE

To 72" Bowl
60,000 GPM, 1400+'

MULTI-STAGE

To 8" Discharge
4800 GPM, 2100'

SELF PRIMER

To 12" Discharge
6400 GPM, 260'

VERTICAL SUMP

To 12" Discharge
9800 GPM, 550'

American-Marsh Pumps

185 Progress Road
Collierville, TN 38017
PH: (800)888-7167
FX: (901)860-2323

Distribution/Service Centers:

Nebraska: 113 South Lincoln Avenue, Hastings, NE 68901 (800)408-7167
California: 3269 East North Building D, Fresno, CA 93725 (800)288-7167
Florida: 2805 Badger Road, Lakeland, FL 33811 (800)444-7167
www.american-marsh.com